20kVA Soundproof Generator

Generating Set	50 Hz
Continuous Power	20 kVA
Standby Power	22 kVA
Noise Level @ 1m / 7m	75 dBA / 63 dBA
Power Factor	cos φ 0.8
Continuous Power	16 kWe
Standby Power	18 kWe
Amps 3 Phase	27 A
Fuel consumption 70% load	3.8 l/h
Engine	**1500 rpm**
Model	Perkins 404D-22G
Continuous Power	18.5 kWm
Standby Power	20 kWm
Aspiration	Turbocharged
Cooling System	Water
Speed Governor	Mechanical
Cylinder Number	4
Displacement	2,216 cm³
Logistic Information	**GX22PE**
Fuel Tank	75 ltr
Weight (Wet)	670 kg
Dimensions (L x W x H)	150 x 80 x 133 cm
Control Panel	**SPG120**
Manual Start	Standard

Features

- Noise Level @ 1m, 75dBA (@7m, 63dBA)
- Autostart DSE CP with MCCB
- VELCB
- Micro Switch Protection over Buss Bar Door
- Oil Extraction Pump
- 3 Way Fuel Valve
- Battery Isolator
- Water Separator Std
- Cental Lifting Hook
- Fork Lift Pockets
- Fully Bunded

Options

- Bulk Fuel Tank
- Battery Charger
- Deep Sea 7210 Auto Start

SPG120 Control Panel

ABIRD GENERATOR HIRE

Power Solutions Nationwide

Link-up Registered Supplier ID 25841

CHAS Accredited Contractor

ISO 9001:2008 SGS

ABIRD has a policy of continuous improvement and therefore reserve the right to change the specification without prior notice.

Head Office: ABIRD Ltd. Ramsgate Road, Sandwich, Kent, CT13 9ND

T. 01304 613 221 W. abird.co.uk E. info@abird.co.uk